RSI-658 INIAY 865 - 928 MHz Global, Passive Transponder

Sirit's RSI-658 antenna was designed for general use applications, and gives strong performance when applied to a variety of materials including cardboard and plastic. Designed for use with NXP UCODE and Alien Higgs 3 ICs, the RSI-658 has options for standard or additional user memory.



Performance Characteristics	
Operating Frequency:	902 - 928 MHz Americas, 4 W EIRP 869.4 - 869.56 MHz Europe, 0.5 W ERP 865.6 - 867.6 MHz Europe, 2 W ERP
Supported Protocol:	ISO 18000-6C
Data Transfer Rate:	Up to 640 kbps
Functionality:	Read/Write
Memory	
Chip Type:	NXP UCODE G2XL; G2XM, Alien Higgs 3
EPC:	96 bits, scaleable
User Memory:	512 bits (G2XM & Higgs 3)
Tag Identifier:	64 bits
Access password:	32 bits
Kill password:	32 bits
EEPROM data retention:	10 years
EEPROM write endurance:	100,000 cycles
Physical Characteristics	
Dimensions (MyL)	
Dimensions (WxL):	Antenna - 93.4 x 4.55 mm (3.677 x 0.179 in.) Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.))
Pitch:	
, ,	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.))
Pitch:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in)
Pitch: Antenna Material Type:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink
Pitch: Antenna Material Type: Yield:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink 95% (Dry); 99.6% (Wet)
Pitch: Antenna Material Type: Yield: Core Size:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink 95% (Dry); 99.6% (Wet) 3 in
Pitch: Antenna Material Type: Yield: Core Size: Quantity/Roll:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink 95% (Dry); 99.6% (Wet) 3 in 5,000 (Dry); 1,000 or 5,000 (Wet)
Pitch: Antenna Material Type: Yield: Core Size: Quantity/Roll: Part Number:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink 95% (Dry); 99.6% (Wet) 3 in 5,000 (Dry); 1,000 or 5,000 (Wet)
Pitch: Antenna Material Type: Yield: Core Size: Quantity/Roll: Part Number: Environment	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink 95% (Dry); 99.6% (Wet) 3 in 5,000 (Dry); 1,000 or 5,000 (Wet) IN-58 (Dry) WI-58 (Wet)
Pitch: Antenna Material Type: Yield: Core Size: Quantity/Roll: Part Number: Environment ESD Voltage Immunity:	Wet Inlay - 103.188 x 9.525 mm (4.063 x 0.375 in.)) 12.7 mm (0.5 in) Printed Silver Ink 95% (Dry); 99.6% (Wet) 3 in 5,000 (Dry); 1,000 or 5,000 (Wet) IN-58 (Dry) WI-58 (Wet) +/- 3kV

For more information contact Sirit tag sales at 1.619.656.2515 or at



About Sirit

Sirit Inc. (TSX: SI) is a leading provider of Radio Frequency Identification (RFID) tags, readers, embedded modules and services, and a leading vertically integrated manufacturer of antennas, inlays and tags, which when integrated with our partners' products are designed to make RFID work. Sirit's core skills in rapid tag design and high quality manufacturing of inlays and labels, coupled with its extensive systems design and integration expertise, enable it to deliver complete, innovative solutions to complex RFID problems across global markets. For more information contact Sirit tag sales at 619.656.2515. or visit www.sirit.com.